

ALTIS EM NA GREASE



GREASE



Electric motor grease

APPLICATIONS

Electric motor grease

- **ALTIS EM NA GREASE** is a non-soap polyurea lubricating grease formulated from paraffinic base oils and selected rust and oxidation inhibitors.
- **ALTIS EM NA GREASE** is formulated without EP additives as required by many electric motor bearing manufacturers. It is recommended for use in antifriction bearings operating at high speeds (10,000 rpm and higher) where the operating temperatures are 150 C (300 F) and higher. It also performs well in bearings at lower temperatures. It is an excellent lubricant for high-speed ball and roller bearings in applications such as alternators, generators, air-conditioning units, starters, electric motors, wheel bearings and other long-life applications where silent operations are desired.

SPECIFICATIONS

- ISO 6743-9: L-XBEHA2
- DIN 51502: K2P-10

ADVANTAGES

Long life with quiet bearings

- Lubrication maintains quiet motor bearings
- Rust and oxidation inhibited for longer bearing life
- Ashless, non-EP and non-staining
- Dyed red for easy identification

TYPICAL CHARACTERISTICS ALTIS EM NA GREASE	
NLGI Grade	2
Appearance, visual	Smooth red grease
Thickener type	Polyurea
Penetration worked, 60x (ASTM D 217)	280
Dropping point, °F (°C) (ASTM D 2265)	500 (260)
Ball bearing grease life, hrs @ 300 F (ASTM D 3336)	3000
Rust prevention (ASTM D-1743)	Pass
Base oil viscosity @ 40°C, cSt (ASTM D 445)	130
Operating range, °F	0 to 275

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418,
Plano, Texas 75075
800-442-5823 or 469-241-0950
www.total-us.com

Altis EM NA Grease #2
Sheet updated: 5/10/2010

5 North Stiles Street
Linden, NJ 07036
908.862.9300 or 800.526.4127
www.total-us.com