



SDS # : 083094

CARTER EP 150

Date of the previous version: 2015-05-12

Revision Date: 2015-10-13

Version 2.01

**WARNING**

May cause an allergic skin reaction

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapours/ spray
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves

Precautionary Statements - Response

Specific treatment (see Section 4 on this label)

Skin

IF ON SKIN: Wash with plenty of soap and water
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse

Precautionary Statements - Disposal

Dispose of contents/ container to an approved waste disposal plant

Unknown Acute Toxicity

No information available

Hazards not otherwise classified (HNOC)

None known

Other information**Physical-Chemical Properties** Contaminated surfaces will be extremely slippery.**Environmental properties** Should not be released into the environment.**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No	Weight %
Long chain alkylamine	^	0-5

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

** The exact percentage (concentration) of composition has been withheld as a trade secret****

Version GNAM



SDS # : 083094

CARTER EP 150

Date of the previous version: 2015-05-12

Revision Date: 2015-10-13

Version 2.01

4. FIRST AID MEASURES**First aid measures for different exposure routes**

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse immediately with plenty of water and seek medical advice.
Skin contact	Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse. Seek medical attention if skin irritation, swelling or redness develops and persists.
Inhalation	Inhalation of high concentrations of vapor or aerosols may cause irritation of the upper respiratory tract.
Ingestion	If swallowed, do not induce vomiting - seek medical advice.

Most important symptoms/effects, acute and delayed

Skin contact	May cause an allergic skin reaction. Avoid contact with skin.
Eye contact	Not classified. May cause eye irritation with susceptible persons.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Itching.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	May cause sensitization of susceptible persons.
---------------------------	---

5. FIRE-FIGHTING MEASURES

<u>Suitable Extinguishing Media</u>	Foam. Carbon dioxide (CO ₂). ABC powder. Water spray.
<u>Unsuitable Extinguishing Media</u>	Do not use a solid water stream as it may scatter and spread fire.
<u>Special Hazard</u>	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.
<u>Explosion Data</u>	
Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.

Version GNAM



SDS # : 083094

CARTER EP 150

Date of the previous version: 2015-05-12

Revision Date: 2015-10-13

Version 2.01

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information

Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Avoid contact with the skin and the eyes. Use personal protective equipment. Evacuate personnel to safe areas. Ensure adequate ventilation.

Other information

See Section 12 for additional information.

Environmental precautions

General Information

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained. Try to prevent the material from entering drains or water courses. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for cleaning up

Dam up. Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use mechanical means such as pumps, skimmers and absorbent materials.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Avoid breathing vapors, mist or gas. Do not use abrasives, solvents or fuels. Do not put product contaminated rags into workwear pockets. Regular cleaning of equipment, work area and clothing is recommended. Avoid prolonged and repeated contact with the skin, especially with used or waste product.

Conditions for safe storage, including any incompatibilities

Version GNAM



SDS # : 083094

CARTER EP 150

Date of the previous version: 2015-05-12

Revision Date: 2015-10-13

Version 2.01

Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture. Keep in properly labeled containers.

Materials to Avoid

Strong oxidizing agents. Reducing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Mineral oil mist:
USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined).

Exposure controls

Engineering Measures

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Individual protection measures, such as personal protective equipment

General Information

If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.

Eye/Face Protection

If splashes are likely to occur, wear: Goggles. Safety glasses with side-shields.

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots.

Hand Protection

Protective gloves. Neoprene gloves. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Hydrocarbon-proof gloves. Fluorinated rubber.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Version GNAM



SDS # : 083094

CARTER EP 150

Date of the previous version: 2015-05-12

Revision Date: 2015-10-13

Version 2.01

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Avoid breathing vapors, mist or gas. Do not use abrasives, solvents or fuels. Do not put product contaminated rags into workwear pockets. Regular cleaning of equipment, work area and clothing is recommended. Avoid prolonged and repeated contact with the skin, especially with used or waste product.

9. PHYSICAL AND CHEMICAL PROPERTIES**Physical and chemical properties**

Color		dark amber	
Physical State @20°C		liquid	
Odor		Oily	
Odor Threshold		No information available	
Property	Values	Remarks	Method
pH		Not applicable	
Melting point/range		No information available	
Boiling point/boiling range		Not applicable	
Flash point	254 °C		Cleveland Open Cup (COC)
	490 °F		ASTM D 92
			Cleveland Open Cup (COC).
			ASTM D 92.
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
upper	-	No information available	
Lower	-	No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Relative density	0.884	@ 15 °C	ASTM D 1298
Density	884 kg/m ³	@ 15 °C	ASTM D 1298
Water solubility		Not applicable	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		Not applicable	
Decomposition temperature		No information available	
Viscosity, kinematic	150 mm ² /s	@ 40 °C	ASTM D 445
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	Not applicable		
Other information			
Specific Gravity	0.884	@ 15 °C	
Freezing Point		No information available	
Pour point	-15 °C		ASTM D 97

Version GNAM



SDS # : 083094

CARTER EP 150

Date of the previous version: 2015-05-12

Revision Date: 2015-10-13

Version 2.01

Fire point

271 °C

ASTM D 92

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to Avoid	Take precautionary measures against static discharges. Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Strong oxidizing agents.
Incompatible Materials	Strong oxidizing agents. Reducing agents.
Hazardous Decomposition Products	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

Information on likely routes of exposure

Principle Routes of Exposure Inhalation, Ingestion, Eye contact, Skin contact.

Numerical measures of toxicity

ATEmix (oral)	5120 mg/kg
ATEmix (dermal)	5120 mg/kg
Inhalation	
ATEmix (inhalation-dust/mist)	5.2 mg/l
ATEmix (inhalation-vapor)	20.6 mg/l

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Long chain alkylamine ^	LD50 612 mg/kg (Rat)	LD50 251 mg/kg (Rabbit)	LC50 (4h) 157 ppm (Rat - gas)

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Itching.

Skin contact May cause an allergic skin reaction. Avoid contact with skin.

Version GNAM



SDS # : 083094

CARTER EP 150

Date of the previous version: 2015-05-12

Revision Date: 2015-10-13

Version 2.01

Eye contact	Not classified. May cause eye irritation with susceptible persons.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause an allergic skin reaction.
Carcinogenicity This product is not classified carcinogenic.

Mutagenicity Contains no ingredient listed as a mutagen.
Reproductive toxicity This product does not present any known or suspected reproductive hazards.
Other adverse effects Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).
Aspiration Hazard Not classified.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Acute aquatic toxicity - Product Information**

No experimental data available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Long chain alkylamine ^	EC50 (72h) 0.44 mg/l (Algae)	LC50 (96h) 1.3 mg/l (Fish)	EC50 (48h) 2.5 mg/l (Daphnia magna)	

Chronic aquatic toxicity - Product Information

No experimental data available

Chronic aquatic toxicity - Component Information

No information available

Effects on terrestrial organisms No experimental data available .**Persistence and degradability****General Information** No information available.

Version GNAM



SDS # : 083094

CARTER EP 150

Date of the previous version: 2015-05-12

Revision Date: 2015-10-13

Version 2.01

Bioaccumulative potential**Product Information** No information available.**logPow** No information available**Component Information**

Chemical Name	log Pow
Long chain alkylamine ^	2.9

Mobility**Soil** Given its physical and chemical characteristics, the product generally shows low soil mobility**Air** Loss by evaporation is limited**Water** The product is insoluble and floats on water**Other adverse effects****General Information** No information available**13. DISPOSAL CONSIDERATIONS****Waste treatment****Waste Disposal Methods** Dispose of in accordance with local regulations.**Contaminated packaging** Dispose of in accordance with local regulations.**14. TRANSPORT INFORMATION****DOT** Not regulated**TDG** Not regulated**MEX** Not regulated**ICAO/IATA** Not regulated**IMDG/IMO** Not regulated**ADR/RID** Not regulated

Version GNAM



SDS # : 083094

CARTER EP 150

Date of the previous version: 2015-05-12

Revision Date: 2015-10-13

Version 2.01

ADN Not regulated**15. REGULATORY INFORMATION**

International Inventories All the substances contained in this product are listed or exempted from listing in the following inventories:
U.S.A. (TSCA)

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	no
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:***

Chemical Name	Weight %	California Prop. 65
Toluene - 108-88-3	<0.1	Developmental Female Reproductive

U.S. State Right-to-Know Regulations

Version GNAM



SDS # : 083094

CARTER EP 150

Date of the previous version: 2015-05-12

Revision Date: 2015-10-13

Version 2.01

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois
Paraffin oils (petroleum), catalytic dewaxed heavy 64742-70-7	X			
Distillates (petroleum), hydrotreated light paraffinic 64742-55-8	X			

16. OTHER INFORMATION

NFPA	Health Hazard 1	Flammability 1	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 1	Flammability 1	Physical Hazard 0	Personal protection X

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2015-10-13
 Revision Note: *** Indicates updated section
 Abbreviations, acronyms

Legend

Section 8
 ACGIH - American Conference of Governmental Industrial Hygienists
 OSHA - Occupational Safety and Health Administration
 NIOSH - National Institute for Occupational Safety and Health
 TLV - Threshold Limit Values
 PEL - Permissible Exposure Limits
 IDHL - Immediately Dangerous to Life or Health concentrations
 TWA - Time Weight Average
 STEL - Short Term Exposure Limits
 S* - Skin notation
 TSCA - Toxic Substance Control Act

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet

Version GNAM