



DYNATRANS MP



Lubricant for transmission systems, hydraulic circuits and oil-bath disc brakes fitted to agricultural tractors, construction machinery and handling systems.

APPLICATIONS

Transmission systems

Hydraulics

Submerged brakes

- Lubrication of mechanical transmission systems requiring a GL4 product.
- Lubrication of automatic transmission systems, torque converters and hydrostatic transmissions.
- Lubrication of power take-offs.
- Application to all hydraulic circuits.
- Lubrication of power-assisted steering systems.
- Lubrication of wet brakes with cellulose liners.

PERFORMANCES

Classifications

Meets manufacturers' specifications

API GL-4
JOHN DEERE JDM J 20A / J20C
FORD M2C 134D / FHNA 2C 201.00
CASE MS 1206 / 1207

CUSTOMER BENEFITS

Wide range of applications

Long component life

- Equally suitable for agricultural machinery and for construction machinery, meaning fewer lubricants need be stocked.
- Excellent low temperature performance (protects friction discs against any risk of binding).

SPECIFICATIONS

DYNATRANS MP	Units	
Kinematic viscosity at 40°C	mm ² /s (cSt)	63
Kinematic viscosity at 100°C	mm ² /s (cSt)	10.8
Viscosity number		153
Pour point	°C	-33

The values of the specifications shown in this table are given as an indication only.

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418,
Plano, Texas 75075
800-442-5823 or 469-241-0950
www.total-us.com

DYNATRANS AC
Sheet updated : 5/10/2010
International Product Data Sheet

5 North Stiles Street
Linden, New Jersey 07036
800-526-4127 or 908-862-9300
www.total-us.com