

FLUID NA H3



Multi-Purpose ATF for most 1979-2007 GM, Ford vehicles

APPLICATIONS

Types of service

- **FLUID NA H3** is recommended for wherever DEXRON® III, DEXRON® II, DEXRON® II-E or Type A fluids are recommended; or wherever MERCON®. M2C138-CJ or M2C166-H fluids are called for.
- **FLUID NA H3** is recommended for applications calling for Allison C-4 fluid and it may be used as “top-off” fluid in automatic transmissions built by Chrysler.
- Other common applications are in hydraulic systems as a wide range hydraulic fluid or as a low to medium quality rotary air compressor fluid.
- Consult your owner’s manual regarding its suitability as ATF in imported vehicles.

PERFORMANCE

Specifications

- Allison C-4
- Meets Allison TES 389 (approval pending)
- Ford M2C138-CJ, and M2C166-H
- GM transmissions calling for Dexron® III or Mercon

CUSTOMER BENEFITS

High technical performance

- Exceptional cleanliness of delicate control valves resulting in trouble-free transmission performance.
- High viscosity index gives excellent performance over a wide temperature range.
- Proper frictional properties provide the required shift feel characteristics.
- Excellent anti-wear, anti-corrosion, anti-foam and oxidation resistance.
- Excellent low temperature fluidity protects against wear under extremely cold operating conditions.

CHARACTERISTICS

TYPICAL PROPERTIES FLUID NA H3	
Color, Visual	Red
Viscosity, cP @ -20°C (-4°F) ASTM D-2983	1400
Viscosity, cP @ -35°C (-31°F) ASTM D-2983	15000
Viscosity, cSt @ 100°C: ASTM D-445	7.2
Viscosity Index ASTM D-2270	175
Pour Point, °C (°F) ASTM D-97	-48 (-55)
Flash Point, °C (°F) ASTM D-93	220 (428)

TOTAL Lubricants USA, Inc.

Fluid NA H3
Sheet updated: 11/25/2014

5 North Stiles Street
Linden, NJ 07036
908.862.9300 or 800.323.3198
www.totallubricantsusa.com