

# MOLDOL CM OILS



FORM RELEASE  
LUBRICATION



**TOTAL**

## Multi-purpose concrete mold release oils

### APPLICATIONS

#### Concrete mold release oils

- **MOLDOL CM (Concrete Mold) OILS** are low to heavy viscosity oils that contain additives that react with the concrete to enhance concrete form release.
- These multipurpose mold release oils are primarily used for demolding concrete materials. The lighter grades may be brushed or sprayed while the heavier grade may require heating for spraying. They aid in clean separation of concrete from various metal, wood, plastic or other types of forms. They contain no solvents.

### SPECIFICATIONS

#### International specifications

- ISO 6743/ Category B

### ADVANTAGES

#### Technical performance

- Good release characteristics
- Non-staining
- Very low VOC (volatile organic compounds)
- Reduces concrete buildup on forms

### TYPICAL CHARACTERISTICS--MOLDOL CM OILS

Grades	12	18	68	320
Specific Gravity @ 60/60°F ASTM D 1298	0.8702	0.874	0.888	0.9071
Density @ 60°F, lbs. /gal. ASTM D 1298	7.25	7.278	7.397	7.554
Viscosity at 40°C, cSt ASTM D 445	12.3	18	68	320
Flash Point, COC, °F (°C) ASTM D 92	363 (184)	378 (192)	464 (240)	584 (307)
Color ASTM D 1500	0.5	L1.0	L3.0	4.0

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418,  
Plano, Texas 75075  
800-442-5823 or 469-241-0950  
www.total-us.com

**Moldol CM Oils**  
Sheet updated: 5/10/2010

5 North Stiles Street  
Linden, NJ 07036  
908.862.9300 or 800.526.4127  
www.total-us.com