

OSYRIS 202 S



METALWORKING



TOTAL

Oily Film Rust Preventative.

APPLICATIONS

- **OSYRIS 202 S** is a petroleum based rust preventative designed to leave a light, oily film that prevents rust and corrosion on metal parts. This film will provide excellent indoor protection from rust and corrosion up to 12 months.
- **OSYRIS 202 S** is a non-staining, low in odor, alkali resistant, and water displacing rust preventative. It can be applied by conventional dip, brush, or spray methods.
- Uses include: preservative for work in process, idle, or stored machine tools, parts, dies, jigs, or bearings. Primarily recommended for preventing electrical shorting and starting up wet motors and in protecting against shorts in electric motors exposed to high humidity.

ADVANTAGES

- Easily removed from parts with petroleum solvents, by vapor degreasing, or by hot alkaline wash (130 °F).
- High flash point.
- Displaces water.
- Non-staining.
- Excellent metal wetting ability.

| TYPICAL CHARACTERISTICS | OSYRIS 202 S |
|-----------------------------|--------------------|
| Appearance | Clear Amber Liquid |
| Color, ASTM D-1500 | 3.5 |
| Odor | Mild Petroleum |
| Viscosity at 40°C, cSt | 14.6 - 16.2 |
| Density @ 60 °F, lbs./gal. | 7.23 |
| Specific Gravity @ 60/60 °F | 0.868 |
| Flash Point, COC, °F | 310 |
| Copper Strip Corrosion | 1A-1B |
| Lubricity Content, % | 5.0 |
| Film Type | Oily |
| Indoor Protection, months | 10 - 12 |

TOTAL Lubricants USA, Inc.

Linden, NJ 07036
5 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198 / 800.526.4127

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198 / 800.526.4127