

PRESLIA 32 - 46 - 68 - 100



Turbine oil

Mineral turbine oils.

APPLICATIONS

**Turbomachines gears
Regulation systems**

- **PRESLIA** oils are specially designed for the lubrication of:
 - turbines: steam, gas, combined cycle, hydraulic
 - gear boxes
 - centrifugal compressors
 - regulation circuits
 - turbochargers with separate oil circuit.

SPECIFICATIONS

International standards
OEM'S

- **ISO 6743-5** THA/THE/TSA/TSE/TGA/TGB/TGE/TGSB
- Depending on their viscosity grade, **PRESLIA** oils meet the requirements of the following classifications and specifications :
 - **ALSTOM** HTGD 90 117
 - **ALSTOM HYDRO** HTWT 600050
 - **GENERAL ELECTRIC** GEK 27070, GEK 28143 B, GEK 46506 E, GEK 32568 G
 - **MAN ENERGIE** ME-TTS 001/18/92
 - **MAN Turbo** SPD 10000494596
 - **SIEMENS** TLV 901304 & TLV 901305
 - **SOLAR** ES 9-224W Class II
 - **SKODA, TURBINY PLZEN**

ADVANTAGES

Long drain intervals
Simplified maintenance
Ageing protection

- High oxidation resistance, antifoam, air and water release performances.
- High antiwear properties allowing the lubrication of the gear boxes driven by the turbine.
- High antirust and anticorrosion performances.
- Important « hydraulic properties » especially hydrolysis stability and filterability (with or without water).

TYPICAL CHARACTERISTICS	METHODS	UNITS	PRESLIA			
			32	46	68	100
Density at 15 °C	ISO 3675	kg/m ³	870	875	884	886
Viscosity at 40 °C	ISO 3104	mm ² /s	32	46	68	100
Viscosity at 100 °C	ISO 3104	mm ² /s	5,4	6,8	8,7	11,4
Viscosity index	ISO 2909	-	100	100	100	100
Flash point	ISO 2592	°C	218	230	240	250
Pour point	ISO 3016	°C	- 12	- 9	- 9	- 9

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS
Industrie & Spécialités
17-07-2012 (supersedes 14-12-2010)
PRESLIA 32-46-68-100
1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from www.quick-fds.com.