

### Section 1: Identification of the substance or mixture and of the supplier

<b>Product Name:</b>	Unleaded Gasoline
<b>SDS Number:</b>	210-001
<b>Synonyms/Other Means of Identification:</b>	Subgrade Gasoline Regular Gasoline Plus Gasoline Premium Gasoline Unleaded Gasoline Conventional Gasoline Oxygenated Gasoline Reformulated Gasoline RFG CVG
<b>Intended Use:</b>	Motor fuel
<b>Manufacturer:</b>	Coffeyville Resources Refining & Marketing A CVR Energy, Inc. Company PO. Box 1566 / 400 North Linden St. Coffeyville, KS 67337
<b>Emergency Health and Safety Number:</b>	Chemtrec: 800-424-9300 (24 Hours)
<b>SDS Information:</b>	Phone: 620-251-4000

### Section 2: Hazard(s) Identification

#### Classification

H224 -- Flammable liquids -- Category 1  
H304 -- Aspiration Hazard -- Category 1  
H315 -- Skin corrosion/irritation -- Category 2  
H336 -- Specific target organ toxicity (single exposure) -- Category 3  
H350 -- Carcinogenicity -- Category 1B  
H361 -- Reproductive Toxicity -- Category 2  
H411 -- Hazardous to the aquatic environment, chronic toxicity -- Category 2

#### Label Elements



#### **DANGER**

**Extremely flammable liquid and vapor. (H224)**  
**Causes skin irritation. (H315)**  
**May be fatal if swallowed and enters airways. (H304)**  
**May cause drowsiness or dizziness. (H336)**  
**May cause cancer. (H350)**  
**Suspected of damaging the unborn child. (H361)**  
**Toxic to aquatic life with long lasting effects. (H411)**

**Precautionary Statement(s):**

Obtain special instructions before use. (P201)  
Do not handle until all safety precautions have been read and understood. (P202)  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking. (P210)  
Keep container tightly closed. (P233)  
Ground/bond container and receiving equipment. (P240)  
Use with explosion-proof equipment. (P241)  
Use only non-sparking tools. (P242)  
Take precautionary measures against static discharge. (P243)  
Avoid breathing dust/fume/gas/mist/vapors/spray. (P261)  
Wash thoroughly after handling. (P264)  
Use only outdoors or in a well-ventilated area. (P271)  
Wear protective gloves / protective clothing / eye protection / face protection. (P280)  
IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. (P303+P361+P353)  
If skin irritation occurs: Get medical advice/attention. (P313)  
Take off contaminated clothing and wash before reuse. (P362)  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. (P301+P310)  
Do NOT induce vomiting. (P331)  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. (P304+P340)  
Call a POISON CENTER or doctor/physician if you feel unwell. (P312)  
In case of fire: Use dry chemical, carbon dioxide, or foam for extinction.(P370+P378)  
Store in a well-ventilated place. Keep cool.(P403+P235)  
Store locked up. (P405)  
Dispose of contents/container to approved disposal facility. (P501)

**Section 3: Composition / Information on Ingredients**

Component	CASRN	Concentration <sup>1</sup>
Gasoline (mixture)	None	85 - 100
Toluene	108-88-3	Up to 10
Xylene	1330-20-7	Up to 10
Benzene	71-43-2	Up to 3

<sup>1</sup> All concentrations are percent by weight

**Section 4: First Aid Measures**

**Eye Contact:** If irritation or redness develops from exposure, flush eyes with clean water. If symptoms persist, seek medical attention.

**Skin Contact:** Remove contaminated shoes and clothing, and flush affected area(s) with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected area(s) thoroughly by washing with mild soap and water or a waterless hand cleaner. If irritation or redness develops, seek medical attention. Wash contaminated clothing before reuse.

**Inhalation (Breathing):** If respiratory symptoms develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. If breathing is difficult, oxygen or artificial respiration should be administered by qualified personnel. If symptoms persist, seek medical attention.

**Ingestion (Swallowing):** Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. If victim is drowsy or unconscious and vomiting, place on the left side with the head down. If possible, do not leave victim unattended and observe closely for adequacy of breathing. Seek medical attention.

**Most important symptoms and effects**

**Acute:** Headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue.

**Delayed:** Dry skin and possible irritation with repeated or prolonged exposure.

**Notes to Physician:** Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to high concentrations of hydrocarbon solvents (e.g., in enclosed spaces or with deliberate abuse). The use of other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs are administered, observe for the development of cardiac arrhythmias.

Federal regulation (29 CFR 1910.1028) specify medical surveillance programs for certain exposures to benzene above the action level or PEL (specified in Section (i)(1)(i) of the Standard). In addition, employees exposed in an emergency situation shall, as described in Section (i)(4)(i), provide a urine sample at the end of the shift for measurement of urine phenol.

## Section 5: Fire-Fighting Measures



### NFPA 704 Hazard Class

**Health:** 1    **Flammability:** 3    **Instability:** 0    (0-Minimal, 1-Slight, 2-Moderate, 3-Serious, 4-Severe)

### HMIS®



The customer is responsible for determining the PPE code for this material.

**Health:** 2\*    **Flammability:** 3    **Physical Hazard:** 0    (0-Minimal, 1-Slight, 2-Moderate, 3-Serious, 4-Severe, \*-Chronic)

**Unusual Fire & Explosion Hazards:** Highly Flammable. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). Vapors may travel considerable distances to a source of ignition where they can ignite, flash back, or explode. May create vapor/air explosion hazard indoors, in confined spaces, outdoors, or in sewers. This product will float and can be reignited on surface water. Vapors are heavier than air and can accumulate in low areas. If container is not properly cooled, it can rupture in the heat of a fire.

**Extinguishing Media:** Dry chemical, carbon dioxide, or foam is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Water may be ineffective for extinguishment, unless used under favorable conditions by experienced fire fighters.

**Fire Fighting Instructions:** For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self-contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8).

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

**Hazardous Combustion Products:** Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of nitrogen and sulfur may also be formed.

See Section 9 for Flammable Properties including Flash Point and Flammable (Explosive) Limits

## Section 6: Accidental Release Measures

**Personal Precautions:** Extremely flammable. Spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition and hot metal surfaces away from spill/release if safe to do so. The use of explosion-proof electrical equipment is recommended. Stay upwind and away from spill/release. Avoid direct contact with material. For large spillages, notify persons down-wind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). See Sections 2 and 7 for additional information on hazards and precautionary measures.

**Environmental Precautions:** Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems, and natural waterways. Use foam on spills to minimize vapors. Use water sparingly to minimize environmental contamination and reduce disposal requirements. If spill occurs on water notify appropriate authorities and advise shipping of any hazard. Spills into or upon navigable waters, the contiguous zone, or adjoining shorelines that cause a sheen or discoloration on the surface of the water, may require notification of the National Response Center (phone number 800-424-8802).

**Methods for Containment and Clean-Up:** Notify relevant authorities in accordance with all applicable regulations. Immediate cleanup of any spill is recommended. Dike far ahead of spill for later recovery or disposal. Absorb spill with inert material such as sand or vermiculite, and place in suitable container for disposal. If spilled on water remove with appropriate methods (e.g. skimming, booms or absorbents). In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

Recommended measures are based on the most likely spillage scenarios for this material; however local conditions and regulations may influence or limit the choice of appropriate actions to be taken. See Section 13 for information on appropriate disposal.

## Section 7: Handling and Storage

**Precautions for safe handling:** Keep away from ignition sources such as heat/sparks/open flame – No smoking. Take precautionary measures against static discharge. Non-sparking tools should be used. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment (see section 8).

Extremely flammable. May vaporize easily at ambient temperatures. The vapor is heavier than air and may create an explosive mixture of vapor and air. Beware of accumulation in confined spaces and low lying areas. Open container slowly to relieve any pressure. The use of explosion-proof electrical equipment is recommended and may be required (see appropriate fire codes). Refer to NFPA-70 and/or API RP 2003 for specific bonding/grounding requirements. Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146. Do not wear contaminated clothing or shoes. Keep contaminated clothing away from sources of ignition such as sparks or open flames.

For use as a motor fuel only. Do not use as a solvent due to its flammable and potentially toxic properties. Siphoning by mouth can result in lung aspiration which can be harmful or fatal.

Gasoline engine exhaust contains hazardous combustion products and has been identified as a possible cancer hazard. Exposure should be minimized to reduce potential risk.

Static Accumulation Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding of tanks, transfer piping, and storage tank level floats are necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. Special care should be given to ensure that special slow load procedures for "switch loading" are followed to avoid the static ignition hazard that can exist when higher flash point material (such as fuel oil or diesel) is loaded into tanks previously containing low flash point products (such as gasoline or naphtha). For more information, refer to OSHA Standard 29 CFR 1910.106, 'Flammable and Combustible Liquids', National Fire Protection Association (NFPA 77, 'Recommended Practice on Static Electricity', and/or the American Petroleum Institute (API) Recommended Practice 2003, 'Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents'.

**Conditions for safe storage:** Keep container(s) tightly closed and properly labeled. Use and store this material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Store only in approved containers. Post area "No Smoking or Open Flame." Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage. Outdoor or detached storage is preferred. Indoor storage should meet OSHA standards and appropriate fire codes.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Before working on or in tanks which contain or have contained this material, refer to OSHA regulations, ANSI Z49.1, and other references pertaining to cleaning, repairing, welding, or other contemplated operations.

## Section 8: Exposure Controls / Personal Protection

Component	ACGIH	OSHA	Other
Gasoline	TWA: 300 ppm STEL :500 ppm (Bulk handling)	---	---
Toluene	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm Peak: 500 ppm (10 min.)	---
Xylene	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm	---
Benzene	TWA: 0.5 ppm STEL: 2.5 ppm (Skin)	Z-2 table TWA: 10 ppm CELL: 25 ppm PEAK: 50 ppm (10 min.)	---

**Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.**

**Engineering controls:** If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

**Eye/Face Protection:** The use of eye protection that meets or exceeds ANSI Z.87.1 is recommended to protect against potential eye contact, irritation, or injury. Depending on conditions of use, a face shield may be necessary.

**Skin/Hand Protection:** The use of gloves impervious to the specific material handled is advised to prevent skin contact. Users should check with manufacturers to confirm the breakthrough performance of their products. Depending on exposure and use conditions, additional protection may be necessary to prevent skin contact including use of items such as chemical resistant boots, aprons, arm covers, hoods, coveralls, or encapsulated suits. Suggested protective materials: Nitrile

**Respiratory Protection:** Where there is potential for airborne exposure above the exposure limit a NIOSH certified air purifying respirator equipped with organic vapor cartridges/canisters may be used.

A respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed whenever workplace conditions warrant a respirator's use. Air purifying respirators provide limited protection and cannot be used in atmospheres that exceed the maximum use concentration (as directed by regulation or the manufacturer's instructions), in oxygen deficient (less than 19.5 percent oxygen) situations, or under conditions that are immediately dangerous to life and health (IDLH).

If benzene concentrations equal or exceed applicable exposure limits, OSHA requirements for personal protective equipment exposure monitoring and training may apply (29cFR1910.1028-Benzene).

**Other Protective Equipment:** Eye wash and quick-drench shower facilities should be available in the work area. Thoroughly clean shoes and wash contaminated clothing before reuse.

**Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals.**

## Section 9: Physical and Chemical Properties

**Note:** Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm). Data represent typical values and are not intended to be specifications.

<b>Appearance:</b>	Clear to red
<b>Physical Form:</b>	Liquid
<b>Odor:</b>	Gasoline
<b>Odor Threshold:</b>	No data
<b>pH:</b>	Not applicable
<b>Vapor Pressure:</b>	330 – 775 mmHG / 7 – 15 psia (Reid VP) @ 100 °F / 37.8°C
<b>Vapor Density (air=1):</b>	3 - 4
<b>Initial Boiling Point/Range:</b>	85 - 437 °F / 29.4 - 225 °C
<b>Melting/Freezing Point:</b>	No data
<b>Solubility in Water:</b>	Insoluble
<b>Partition Coefficient (n-octanol/water) (Kow):</b>	No data
<b>Specific Gravity (water=1):</b>	0.73 @ 60°F (15.6°C)
<b>Evaporation Rate (nBuAc=1):</b>	>1
<b>Flash Point:</b>	-45 °F / -42.8 °C
<b>Test Method:</b>	Tag Closed Cup (TCC)
<b>Lower Explosive Limits (vol % in air):</b>	1.4
<b>Upper Explosive Limits (vol % in air):</b>	7.6
<b>Auto-ignition Temperature:</b>	536 °F / 446.7 °C

## Section 10: Stability and Reactivity

**Stability:** Stable under normal ambient and anticipated conditions of use.

**Conditions to Avoid:** Avoid high temperatures and all sources of ignition. Prevent vapor accumulation.

**Materials to Avoid (Incompatible Materials):** Avoid contact with strong oxidizing agents and strong reducing agents.

**Hazardous Decomposition Products:** Not anticipated under normal conditions of use.

**Hazardous Polymerization:** Not known to occur.

## Section 11: Toxicological Information

### Information on Toxicological Effects of Substance/Mixture

<u>Acute Toxicity</u>	<u>Hazard</u>	<u>Additional Information</u>	<u>LC50/LD50 Data</u>
Inhalation	Expected to have a low degree of toxicity by inhalation	----	> 5.2 mg/L (vapor)
Skin Absorption	Unlikely to be harmful	----	3.75 g/kg
Ingestion (Swallowing)	Unlikely to be harmful	----	14 g/kg

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Skin Corrosion/Irritation:** Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

**Serious Eye Damage/Irritation:** Causes mild eye irritation. .

**Signs and Symptoms:** Effects of overexposure can include slight irritation of the respiratory tract, nausea, vomiting, and signs of nervous system depression (e.g., headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue). Continued exposure to high concentrations can result in vomiting, cardiac irregularities and sudden loss of consciousness.

**Skin Sensitization:** Not expected to be a skin sensitizer.

**Respiratory Sensitization:** No information available.

**Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness and dizziness.

**Specific Target Organ Toxicity (Repeated Exposure):** Not expected to cause organ effects from repeated exposure. Two year inhalation studies of wholly vaporized unleaded gasoline, and 90 days studies of various petroleum naphthas, did not produce significant target organ toxicity in laboratory animals. Nephropathy in male rats, characterized by the accumulation of alpha-2-u- globulin in epithelial cells of the proximal tubules was observed, however follow-up studies suggest that these changes are unique to the male rat.

**Carcinogenicity:** May cause cancer. Two year inhalation studies of vaporized unleaded gasoline produced an increased incidence of kidney tumors in male rats and liver tumors in female mice. Repeated skin application of various petroleum naphthas in mice for two years resulted in an increased incidence of skin tumors but only in the presence of severe skin irritation. Follow-up mechanistic studies suggest that the occurrence of these tumors may be the consequence of promotional processes and not relevant to human risk assessment. Epidemiology data collected from a study of more than 18,000 petroleum marketing and distribution workers showed no increased risk of leukemia, multiple myeloma, or kidney cancer from gasoline exposure. Unleaded gasoline has been identified as a possible carcinogen by the International Agency for Research on Cancer. It also contains benzene, a carcinogen (see below).

**Germ Cell Mutagenicity:** Not expected to cause heritable genetic effects. Gasoline was negative in microbial mutagenicity and unscheduled DNA tests in rat hepatocytes. Gasoline did not induce chromosome aberration in vivo in rat bone marrow cells and was negative in mouse dominant lethal assay. However, Benzene, a component, may cause heritable genetic effects (see below).

**Reproductive Toxicity:** Not expected to cause reproductive toxicity. No evidence of developmental toxicity was found in pregnant laboratory animals (rats and mice) exposed to high vapor concentrations of unleaded gasoline and petroleum naphthas via inhalation. A two-generation reproductive toxicity study of vapor recovery gasoline did not adversely affect reproductive function or offspring survival and developments. However, Toluene, a component, is suspected of damaging the unborn child (see below).

**Other Comments:** Gasoline engine exhaust has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans.

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as solvent or Painter's Syndrome). Intentional misuse by deliberately concentrating and inhaling this material may be harmful or fatal.

### Information on Toxicological Effects of Components

#### Toluene

**Carcinogenicity:** Exposure of rats and mice to toluene at concentrations ranging from 120-1200 ppm for two years did not demonstrate evidence of carcinogenicity. Toluene has not been listed as a carcinogen by IARC.

**Target Organs:** Epidemiology studies suggest that chronic occupational overexposure to toluene may damage color vision. Subchronic and chronic inhalation studies with toluene produced kidney and liver damage, hearing loss and central nervous system (brain) damage in laboratory animals. Intentional misuse by deliberate inhalation of high concentrations of toluene has been shown to cause liver, kidney, and central nervous system damage, including hearing loss and visual disturbances.

**Reproductive Toxicity:** Exposure to toluene during pregnancy has demonstrated limited evidence of developmental toxicity in laboratory animals. Decreased fetal body weight and increased skeletal variations in both inhalation and oral studies, but only at doses that were maternally toxic. No fetal toxicity was seen at doses that were not maternally toxic. Decreased sperm counts have been observed in male rats in the absence of a reduction in fertility. Toluene has been reported to cause mental or growth retardation in the children of solvent abusers who directly inhale toluene during pregnancy.

#### Benzene

**Carcinogenicity:** Benzene is an animal carcinogen and is known to produce acute myelogenous leukemia (a form of cancer) in humans. Benzene has been identified as a human carcinogen by IARC, the US National Toxicology Program and the US Occupational Safety and Health Administration.

**Target Organs:** Prolonged or repeated exposures to benzene vapors can cause damage to the blood and blood forming organs, including disorders like leukopenia, thrombocytopenia and aplastic anemia.

**Reproductive Toxicity:** Some studies in occupationally exposure women have suggested benzene exposure increased risk of miscarriage and stillbirth and decreased birth weight an gestational age. The size of the effects detected in these studies was small and ascertainment of exposure and outcome in some cases relied on self-reports, which may limit the reliability of these results.

**Germ Cell Mutagenicity:** Benzene exposure has resulted in chromosomal aberration in human lymphocytes and animal bone marrow cells. Exposure has also been associated with chromosomal aberration in sperm cells in human and animal studies.

### Information on Toxicological Effects of Potential Components

#### Xylenes

**Target Organs:** Rats exposed to xylenes at 800, 1000 or 1200 ppm 14 hours daily for 6 weeks demonstrated high frequency hearing loss. Another study in rats exposed to 1800 ppm 8 hours daily for 5 days demonstrated middle frequency hearing loss.

**Reproductive Toxicity:** Both mixed xylenes and the individual isomers produced limited evidence of developmental toxicity in laboratory animals. Inhalation and oral administration of xylene resulted in decreased fetal weight, increased incidence of delayed ossification, skeletal variations and resorptions, but no evidence of teratogenicity.

#### n-Hexane

**Target Organs:** Excessive exposure to n-hexane can result in peripheral neuropathies. The initial symptoms are symmetrical sensory numbness and paresthesias of distal portions of the extremities. Motor weakness is typically observed in muscles of the toes and fingers but may also involve muscles of the arms, thighs and forearms. The onset of these symptoms may be delayed for several months to a year after the beginning of exposure. The neurotoxic properties of n-hexane are potentiated by exposure to methyl ethyl ketone and methyl isobutyl ketone.

**Reproductive Toxicity:** Prolonged exposure to high concentrations of n-hexane (>1,000 ppm) resulted in decreased sperm count and degenerative changes in the testes of rats but not those of mice.

#### **Ethyl Benzene**

**Carcinogenicity:** Rats and mice exposed to 0, 75, 250, or 750 ppm ethyl benzene in a two year inhalation study demonstrated limited evidence of kidney, liver, and lung cancer. Ethyl benzene has been listed as a possible human carcinogen by IARC.

**Target Organs:** In rats and mice exposed to 0, 75, 250, or 750 ppm ethyl benzene in a two year inhalation study there was mild damage to the kidney (tubular hyperplasia), liver (eosinophilic foci, hypertrophy, necrosis), lung (alveolar epithelium metaplasia), thyroid (hyperplasia), thyroid (hyperplasia) and pituitary (hyperplasia). In animal models (particularly rats), ethyl benzene affects the auditory function mainly in the cochlear mid-frequency range and ototoxicity was observed after combined exposure to noise and ethyl benzene. There is no evidence of either ethyl benzene-induced hearing losses or ototoxicity with combined exposure to ethyl benzene and noise in workers.

## **Section 12: Ecological Information**

**Toxicity:** Acute aquatic toxicity studies on samples of gasoline and naphtha streams show acute toxicity values greater than 1 mg/L and mostly in the range 1-100 mg/L. These tests were carried out on water accommodated fractions, in closed systems to prevent evaporative loss. Results are consistent with the predicted aquatic toxicity of these substances based on their hydrocarbon composition. These substances should be regarded as toxic to aquatic organisms, with the potential to cause long term adverse effects in the aquatic environment. Classification: H411; Chronic Cat 2.

**Persistence and Degradability:** The hydrocarbons in this material are not readily biodegradable but are regarded as inherently biodegradable since their hydrocarbon components can be degraded by microorganisms.

**Bioaccumulative Potential:** Log Kow values measured for the hydrocarbon components of this material range from 3 to greater than 6 and therefore are regarded as having the potential to bioaccumulate. In practice, metabolic processes or physical properties may prevent this effect or limit bioavailability.

**Mobility in Soil:** On release to water, hydrocarbons will float on the surface and since they are sparingly soluble, the only significant loss is volatilization to air. In air, these hydrocarbons are photodegraded by reaction with hydroxyl radicals with half lives varying from 6.5 days for benzene to 0.5 days for n-dodecane.

**Other Adverse Effects:** None anticipated.

## **Section 13: Disposal Considerations**

The generator of a waste is always responsible for making proper hazardous waste determinations and needs to consider state and local requirements in addition to federal regulations.

This material, if discarded as produced, would not be a federally regulated RCRA "listed" hazardous waste. However, it would likely be identified as a federally regulated RCRA hazardous waste for the following characteristic(s) shown below. See Sections 7 and 8 for information on handling, storage and personal protection and Section 9 for physical/chemical properties. It is possible that the material as produced contains constituents which are not required to be listed in the MSDS but could affect the hazardous waste determination. Additionally, use which results in chemical or physical change of this material could subject it to regulation as a hazardous waste.

Container contents should be completely used and containers should be emptied prior to discard. Container residues and rinseates could be considered to be hazardous wastes.

**EPA Waste Number(s)**

- D001 - Ignitability characteristic

**Section 14: Transport Information**

**U.S. Department of Transportation (DOT)**

**Shipping Description:** *Aquatic toxicity studies indicate this material may be classified as a Marine Pollutant under IMDG Code. It is not currently regulated as a marine pollutant by the USDOT. If there is not a Shipping Description or other DOT marking, labeling, placarding and packaging references shown in this section, it is not regulated as a hazardous material by the USDOT.*

**Non-Bulk Package Marking:** UN1203, Gasoline., 3, II  
**Non-Bulk Package Labeling:** Gasoline, UN1203  
**Bulk Package/Placard Marking:** Flammable liquid  
**Packaging - References:** Flammable / 1203  
49 CFR 173.150; 173.202; 173.242  
*(Exceptions; Non-bulk; Bulk)*

**Hazardous Substance:** None  
**Emergency Response Guide:** 128  
**Note:** *Container(s) greater than 5 liters (liquids) or 5 kilograms (solids), shipped by water mode and ALL bulk shipments may require the shipping description to contain the "Marine Pollutant" notation [49 CFR 172.203(l)] and the container(s) to display the [Marine Pollutant Mark] [49 CFR 172.322].*

**Section 15: Regulatory Information**

**CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs (in pounds):**

This material does not contain any chemicals subject to the reporting requirements of SARA 302 and 40 CFR 372.

**CERCLA/SARA - Section 311/312 (Title III Hazard Categories)**

**Acute Health:** Yes  
**Chronic Health:** Yes  
**Fire Hazard:** Yes  
**Pressure Hazard:** No  
**Reactive Hazard:** No

**CERCLA/SARA - Section 313 and 40 CFR 372:**

This material contains the following chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372:

Component	Concentration <sup>1</sup>	de minimis
Toluene	Up to 10	1.0%
Xylenes	Up to 10	1.0%
Benzene	Up to 3	0.1%
Ethyl Benzene	<1	0.1%
Hexane	<1	1.0%

**EPA (CERCLA) Reportable Quantity (in pounds):**

EPA's Petroleum Exclusion applies to this material - (CERCLA 101(14)).

**California Proposition 65:**

Warning: This material may contain detectable quantities of the following chemicals, known to the State of California to cause cancer, birth defects or other reproductive harm, and which may be subject to the warning requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

Component	Type of Toxicity
Toluene	Developmental Toxicant Female Reproductive Toxicant
Benzene	Developmental Toxicant Male Reproductive Toxicant Cancer
Ethyl Benzene	Cancer

**International Hazard Classification**

**Canada:**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the Regulations.

**WHMIS Hazard Class:**

B2 - Flammable Liquids  
D2A  
D2B

**National Chemical Inventories**

All components are either listed on the US TSCA Inventory, or are not regulated under TSCA  
All components are either on the DSL, or are exempt from DSL listing requirements

**Section 16: Other Information**

**Date of Issue:** 06-Apr-2015  
**Status:** Final  
**Previous Issue Date:** 30-Jan-2014  
**Revised Sections or Basis for Revision:** Section 5: Added HMIS  
**SDS Number:** 210 -001

**Guide to Abbreviations:**

ACGIH = American Conference of Governmental Industrial Hygienists; CASRN = Chemical Abstracts Service Registry Number; CEILING = Ceiling Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; EPA = Environmental Protection Agency; GHS = Globally Harmonized System; IARC = International Agency for Research on Cancer; INSHT = National Institute for Health and Safety at Work; IOPC = International Oil Pollution Compensation; LEL = Lower Explosive Limit; NE = Not Established; NFPA = National Fire Protection Association; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; PEL = Permissible Exposure Limit (OSHA); SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit (15 minutes); TLV = Threshold Limit Value (ACGIH); TWA = Time Weighted Average (8 hours); UEL = Upper Explosive Limit; WHMIS = Worker Hazardous Materials Information System (Canada)

**Disclaimer of Expressed and Implied Warranties:**

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.